



- High brightness 0.8"LED display range-1999~9999/-19999~99999; decimal point selectable.
- Simulate analog output signal by front keys.
- High stability, non-flammable case (PC), high safety.
- CE approval.

SPECIFICATION

- ◆ Display Screen: High brightness red LED; 20.3mm(0.8")
- ◆ Display Range: -9999~9999 / -99999~99999
- ◆ Parameters Setting: Push buttons
- ◆ Back Up Memory: EEPROM
- ◆ Analog Output Resolution: 16 bit
- ◆ Output Response Time: <250 msec (0~90%)
- ◆ Output Capability: Voltage Output: <20mA
Current Output: <10V
- ◆ Temperature Coefficient: 100ppm /°C (0~60°C)
- ◆ Operating Temperature: 0~60°C
- ◆ Operating Humidity: 20~90% RH (non-condensing)
- ◆ Storage Temperature: -10~70°C
- ◆ Storage Humidity: 20~90% RH (non-condensing)
- ◆ Power Supply: AC/DC100~240V ; DC 22~50V
- ◆ Power Consumption: 6.5VA
- ◆ Surge Test: 2KVac / 1min (Input / Power)
- ◆ Dimensions: 96(W)*48(H)*85(D) mm
- ◆ Weight: About 300 g

ORDER INFORMATION

MG4/MG5 - Code1 - Code2

Code1	Aux. Power	Code2	Analog Output
A	AC/DC100-240V	A	4-20mA
C	DC 22-50 V	V	0-10V
		O	Other

WIRING CONNECTION

