



- Accuracy 0.015% F.S. ± 3 digit.
- Measuring DCA/ DCV/ Potentiometer...
- Programmable rate -999999~999999 digit.
- Decimal point can be modified.
- Dimension small and High stability.



SPECIFICATION

- ◆ Measuring accuracy : 0.015% F.S. ± 3 digit
- ◆ Sampling time : 20 cycles/sec.
- ◆ Display average times : 1~99 times adjustable
- ◆ Readout range : -999999~999999 digit adjustable
- ◆ Zero (offset) range : -999~999 digit adjustable
- ◆ Span (scale) range : -999~999 digit adjustable
- ◆ Over input indication : " doFL " or "-doFL"
- ◆ Polarity display : When input is negative " POL " display
- ◆ Display : Red high efficiency LEDs high 7.68mm(0.3")
- ◆ Temp. coefficient : 20ppm/°C (0~50°C)
- ◆ Parameter setting : Touch switches
- ◆ Memory mode : Non-volatile E² PROM memory
- ◆ Dielectric strength : 1KVac/1 min. (input/power)
- ◆ Operating condition : 0~50°C (20 to 90% RH non-condensed)
- ◆ Storage condition : 0~70°C (20 to 90% RH non condensed)
- ◆ Outside dimension : 24x48x48.5mm
- ◆ Case material : ABS

WIRING CONNECTION



ORDER INFORMATION

DC6S-AS - **Code1** - **Code2** - **Code3**

C1	Input Type	C2	DCV	C2	DCV	C2	DCA	C2	Potentiometer	C3	Aux.Power
A	DC	11	0~±50mV	16	0~±100V	24	0~±20mA	33	0~100%	A	DC5V(Isolating)
D	Potentiometer	12	0~±5V	17	0~±600V	25	0~±1A	39	SPECIFIED	B	DC12V(Isolating)
		13	0~±10V	19	SPECIFIED	26	0~±5A			C	AC/DC20~260V(Isolating)
		15	0~±50V			29	SPECIFIED				•LESS ±10% for DC Input •LESS 1VA for Input

DIMENSION

