



SIDE VIEW

- Current: 5~400A
- Suit for high distortion wave form devices (Inverter, Motor, SCR...)
- 4 times peak value
- Tolerance <0.5% by 4~20mA
- Easily installation, suit for any application

SPECIFICATION

◆ Accuracy:	$\pm 0.5\%$ RO
◆ Output Signal:	DC 4~20mA(2Wires)
◆ Power Supply:	DC 5~40V(2Wire System)
◆ Input Frequency:	10~400Hz.
◆ Input Resistance:	760 Ω (Supply DC 24V)
◆ Isolation:	2.6KV/Min(Input/Output /Case)
◆ Surge Test:	5KV(Isolated Cable)
◆ Insulation Resistance:	$\geq 100\Omega$ /Min with DC 500V)
◆ Temperature Coefficient:	$\leq 0.01\%$ FS/ $^{\circ}\text{C}$ (100PPM)
◆ Response Time:	$\leq 400\text{ms}$
◆ Long Time Stability:	$\leq 0.1\%$ / year
◆ Adjustment:	$\leq \pm 5\%$ (Zero and Span)
◆ Operating Temp.:	-10 $^{\circ}\text{C}$ ~55 $^{\circ}\text{C}$ (20~95%RH non-condensing)
◆ Installation:	Din rail
◆ Storage Temp.:	-40 $^{\circ}\text{C}$ ~75 $^{\circ}\text{C}$ (20~95%RH non-condensing)
◆ Housing Material:	Flame-proof ABS housing suit for UL 94 CLASS V - O.

ORDER INFORMATION

PCT - [Code1] - [Code2]

Code1 Input Current				Code2 Aux. Power	
A	AC 0-5A 2T	H	AC 0-75A	1	DC24V(2Wire)
B	AC 0-10A	I	AC 0-100A	2	Option
C	AC 0-15A	J	AC 0-150A		
D	AC 0-20A	K	AC 0-200A		
E	AC 0-30A	L	AC 0-250A		
F	AC 0-40A	M	AC 0-300A		
G	AC 0-50A	N	AC 0-400A		
Y	Option				

Input Current	Dip Switch Position											
	1	2	3	4	5	6	7	8	9	10	11	12
AC 0-5A 2T	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
AC 0-10A	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
AC 0-15A	ON											
AC 0-20A	ON	ON										
AC 0-30A	ON	ON	ON									
AC 0-40A	ON	ON	ON	ON								
AC 0-50A	ON	ON	ON	ON	ON							
AC 0-75A	ON	ON	ON	ON	ON	ON						
AC 0-100A	ON	ON	ON	ON	ON	ON	ON					
AC 0-150A	ON	ON	ON	ON	ON	ON	ON	ON				
AC 0-200A	ON	ON	ON	ON	ON	ON	ON	ON	ON			
AC 0-250A	ON	ON	ON	ON	ON	ON	ON	ON	ON	ON		
AC 0-300A	ON	ON	ON	ON	ON	ON	ON	ON	ON	ON	ON	
AC 0-400A	ON	ON	ON	ON	ON	ON	ON	ON	ON	ON	ON	ON

WIRING CONNECTION

