


- High brightness 0.32" LCD display: 0~99999999
- Backup memory by replaceable internal battery
- DIN size 24 x 48 mm; easy to install

SPECIFICATION

- | | |
|----------------------------|----------------------------------|
| ◆ Display Screen: | High brightness LCD; 8mm (0.32") |
| ◆ Display Range: | 0~99999999 |
| ◆ Back Up Memory: | Internal battery, replaceable |
| ◆ Temperature Coefficient: | 100ppm / °C (0~60°C) |
| ◆ Operating Temperature: | 0~40°C |
| ◆ Operating Humidity: | 20~90% RH (non-condensing) |
| ◆ Storage Temperature: | -10~55°C |
| ◆ Storage Humidity: | 20~90% RH (non-condensing) |
| ◆ Power Supply: | Internal battery, replaceable |
| ◆ Weight: | About 35g |

WIRING CONNECTION



ORDER INFORMATION

L248T- Code1

Code1	Display Range		
06	99999999D	02	9999D.59H.59M
11	99999999H	07	9999H.59M.59S
14	99999999M	03	99D-59H-59M
15	99999999S	08	99H-59M-59S
04	999999D.59H	01	99D.59H.59M.59S
09	999999H.59M		
12	999999M.59S		
05	99999D-59H		
10	99999H-59M		
13	99999M-59S		